

PRODUCT DESCRIPTION

Power Supply Requirements

- AC Working Voltage: 230V AC
- AC Working Frequency: 50/60 Hz
- Voltage asymmetry: no more than 5%
- Voltage distortion rate: non-sinusoidal content does not exceed 10% of 230V

Power Supply Requirements

- Working environmental temperature: -20°C~+50°C
- Relative humidity: 5% to 95%
- Installation vertical tendency: $\leq 5^\circ$
- Altitude: $\leq 2,000$ meters
- No strong vibration, shock, electromagnetic interference

Technical Characteristics

- Start charging modes: RFID / APP
- Communication mode: Wi-Fi (only 2.4GHz)
- Display mode: 2.4 inch screen
- Perfect protection functions

DETAILED DESCRIPTION OF PRODUCT PERFORMANCE

Model	NEG-1P32-M3T2-C1/NEG-3P16-M3T2-C1/NEG-3P32-M3T2-C1
Rated Power	7kW / 11kW / 22kW _{Text}
Dimension	300 x 160 x 120 mm
Weight	Approximately 4.3 kg
Installation	Wall-mounted
Technical Parameters	Input Voltage: 220-240 VAC(1-phase) / 400 VAC(3-phase)
	Input Model: Single-phase, L+N+PE / Three-phase, L1+L2+L3+N+PE
	Output Current: 32A max
	Frequency: 50/60 Hz
	Output Voltage: 220-240 VAC(1 phase) / 400 VAC(3-phase)
	IP and IK rating: IP55
	Charging Mode: Model 3, Case C
Codes and Standards	IEC61851 / IEC 62196 / TR-25 / CB Scheme(ILAC-MRA)